

Action



361 LT








Total length including drawbar (mm) 5194 (17'0") Body length (mm) 4010 (13'2") Internal length (mm) 3610 (11'10") Total width (mm) 2196 (7'2") Internal width (mm) 2080 (6'10") Total height (mm) 2545 (84") Internal height (mm) 1950 (6'5") ATM Weight (kg) 1400* Tare Weight (kg) 1000* Payload (kg) 400* Maximum Allowable Hitch Weight (kg) 100* Fresh water storage (L) 50 Chassis ✓ Number of axles 1 Al-KO hot dipped galvanised chassis ✓ AL-KO independent rubber suspension (IRS) axle ✓ AL-KO shock absorbers ✓ AL-KO over-run braking system ✓		
Body length (mm) A010 (13'2") Internal length (mm) 3610 (11'10") Total width (mm) 2080 (610") Total width (mm) 2080 (610") Internal width (mm) 2545 (84") Internal height (mm) 2545 (84") Internal height (mm) ATM Weight (kg) 11000* Payload (kg) 400* Maximum Allowable Hitch Weight (kg) 1000* Presh water storage (L) Chassis Number of axles 1. AL-KO hot dipped galvanised chassis AL-KO hot dipped galvanised chassis AL-KO shock absorbers AL-KO shock absorbers AL-KO word-run braking system AL-KO wind-down stabiliser legs AL-KO wind-down stabiliser legs AL-KO wind-down stabiliser legs AL-KO injecky wheel Drawbar cover, impact resistant ABS Alloy wheels Version of XPS styrofoam and EPS styropor to floor, walls and roof Frints a rear walls - Impact resistant ABS Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with heia resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with threathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Fintry door 2-part with integrated flyscreen (51cm wide) Integrated alluminium tent profile to side walle primeter Lugage door on passenger side (light dimensions)	Dimensions & Weights	- 10 1 (1 = 10 II)
Internal length (mm) Total width (mm) Total width (mm) 2196 (772') Total height (mm) 2280 (610') Total height (mm) 2585 (84') Internal height (mm) 2585 (84') Internal height (mm) 1950 (65'7) Total height (kg) 1000* Payload (kg) 1000* Payload (kg) 400* Maximum Allowable Hitch Weight (kg) 100* Fresh water storage (L) 50 Chassis Number of axles AL-KO of dipped galvanised chassis AL-KO independent rubber suspension (IRS) axle AL-KO hot dipped galvanised chassis 4- AL-KO axbox hox absorbers AL-KO owind-down stabiliser legs AL-KO owind-down stabiliser legs AL-KO owind-down stabiliser legs AL-KO ginch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with heir legistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with heir greated privacy blinds, flyscreens and decorative curtains included - Centry and or 2-part with integrated flyscreen (51cm wide) Integrated alluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	3 3 ()	, ,
Total width (mm) 2196 (72") Internal width (mm) 2080 (610") Total height (mm) 12545 (84") Internal height (mm) 11950 (65") ATM Weight (kg) 11950 (65") ATM Weight (kg) 11000* Payload (kg) 1000* Payload (kg) 1000* Maximum Allowable Hitch Weight (kg) 1000* Maximum Allowable Hitch Weight (kg) 1000* Fresh water storage (L) 50 Chassis Number of axles 11 AL-KO hot dipped galvanised chassis 11 AL-KO hot dipped galvanised chassis 11 AL-KO hot dipped galvanised chassis 12 AL-KO anti-sway coupling 12 AL-KO anti-sway coupling 12 AL-KO anti-sway coupling 12 AL-KO wind-down stabiliser legs 12 AL-KO 8 inch jockey wheel 12 Drawbar cover, impact resistant ABS 12 ALIOy wheels 12 Tyre size 1858 R14 C Caravan Body Side walls skirtings in thermoformed ABS 15 Inish - Polyester sealed FRP 15 Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof 15 Front & rear walls - Impact resistant ABS 2 Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof 15 Front & rear walls - Impact resistant ABS 2 Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof 15 Front & rear walls - Impact resistant ABS 2 Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof 15 Front & rear walls - Impact resistant ABS 2 Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof 15 Front & rear walls - Impact resistant ABS 2 Insulation - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior 15 Floor - Structural sandwich panel with heathable kiln dried plywood Interior 15 Floor - Structural sandwich panel with heathable kiln dried plywood Interior 15 Floor - Structural sandwich panel with heathable kiln dried plywood Interior 15 Floor - Structural sandwich panel with heathable kiln dried plywood Interior 15 Floor - Structural sandwich panel with heathable kiln dried plywood Interior 15 Floor - Structural sandwich panel with heathable kiln dried plywood Interior 15 Floor - Structu	, , ,	
Internal width (mm) Internal width (mm) Internal height (kg) Internal height (kg) Internal height (kg) Internal Weight (kg) Internal Weight (kg) Internal Allowable Hitch Weight (kg) Internal Body States	· , ,	
Total height (mm) 2545 (84") Internal height (mm) 1950 (65") ATM Weight (kg) 1000* Payload (kg) 1000* Payload (kg) 400* Maximum Allowable Hitch Weight (kg) 1000* Fresh water storage (L) 50 Chassis Number of axles 1 1 AL-KO not dipped galvanised chassis 1 1 AL-KO not dipped galvanised chassis 1 1 AL-KO not dipped galvanised chassis 1 1 AL-KO shock absorbers 1 1 AL-KO shock absorbers 1 1 AL-KO wind-down stabiliser legs 1 1 AL-KO wind-down stabiliser legs 1 1 AL-KO wind-down stabiliser legs 1 1 AL-KO a linch jockey wheel 1 1 Drawbar cover, impact resistant ABS 1 1 AL-KO a ship system 1 1 AL-KO wind-down stabiliser legs 1 1 AL-KO wind-down stabiliser legs 1 1 AL-KO ship system 1 1 AL-KO wind-down stabiliser legs		, ,
Internal height (mm) Internal height (kg) Intoweight (kg) Intoweight (kg) Intoweight (kg) Payload (kg) Maximum Allowable Hitch Weight (kg) Intoweight (kg) Maximum Allowable Hitch Weight (kg) Intoweight (kg) Maximum Allowable Hitch Weight (kg) Intoweight	Internal width (mm)	2080 (6'10")
ATM Weight (kg) 1400* Tare Weight (kg) 1000* Payload (kg) 400* Maximum Allowable Hitch Weight (kg) 1000* Fresh water storage (L) 50 Chassis Number of axles 11 AL-KO hot dipped galvanised chassis 1 AL-KO hot dipped galvanised chassis 1 AL-KO shock absorbers 1 AL-KO shock absorbers 1 AL-KO over-run braking system 1 AL-KO over-run braking system 1 AL-KO anti-sway coupling 1 AL-KO wind-down stabiliser legs 1 AL-KO shind-down stabiliser	Total height (mm)	2545 (8'4")
Tare Weight (kg) 1000* Payload (kg) 400* Maximum Allowable Hitch Weight (kg) 100* Fresh water storage (L) 50 Chassis Number of axles 1 AL-KO hot dipped galvanised chassis 1 AL-KO independent rubber suspension (IRS) axle	Internal height (mm)	1950 (6'5")
Payload (kg) Maximum Allowable Hitch Weight (kg) 100* Fresh water storage (L) 50 Chassis Number of axles AL-KO hot dipped galvanised chassis AL-KO independent rubber suspension (IRS) axle AL-KO shock absorbers AL-KO shock absorbers AL-KO wer-run braking system AL-KO over-run braking system AL-KO wind-down stabiliser legs AL-KO wind-down stabiliser legs AL-KO wind-down stabiliser legs AL-KO wind-down stabiliser legs AL-KO wind-sover, impact resistant ABS AL-KO weels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Isusulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Firstry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions)	ATM Weight (kg)	1400*
Maximum Allowable Hitch Weight (kg) 100* Fresh water storage (L) 50 Chassis Number of axles AL-KO hot dipped galvanised chassis	Tare Weight (kg)	1000*
Fresh water storage (L) 50 Chassis Number of axles 1 AL-KO hot dipped galvanised chassis	Payload (kg)	400*
Chassis Number of axles AL-KO hot dipped galvanised chassis AL-KO independent rubber suspension (IRS) axle AL-KO shock absorbers AL-KO over-run braking system AL-KO over-run braking system AL-KO wind-down stabiliser legs AL-KO wind-wind-down stabiliser legs AL-KO wind-down stabiliser leg	Maximum Allowable Hitch Weight (kg)	100*
Number of axles AL-KO hot dipped galvanised chassis AL-KO independent rubber suspension (IRS) axle AL-KO shock absorbers AL-KO osor-run braking system AL-KO over-run braking system AL-KO anti-sway coupling AL-KO anti-sway coupling AL-KO anti-sway coupling AL-KO 8 inch jockey wheel Prawbar cover, impact resistant ABS Alloy wheels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Firty door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	Fresh water storage (L)	50
AL-KO hot dipped galvanised chassis AL-KO independent rubber suspension (IRS) axle AL-KO shock absorbers AL-KO over-run braking system AL-KO anti-sway coupling AL-KO wind-down stabiliser legs AL-KO wind-down stabiliser legs AL-KO 8 inch jockey wheel AL-KO 9 inch jockey wheel AL-KO	Chassis	
AL-KO independent rubber suspension (IRS) axle AL-KO shock absorbers AL-KO over-run braking system AL-KO over-run braking system AL-KO anti-sway coupling AL-KO wind-down stabiliser legs AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS AL-KO 8 inch jockey wheel Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	Number of axles	1
AL-KO shock absorbers AL-KO over-run braking system AL-KO anti-sway coupling AL-KO wind-down stabiliser legs AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size Tyre size Tyre size Tyre size Tyre size Tyre size Tyre size Tyre size Tyre siz	AL-KO hot dipped galvanised chassis	✓
AL-KO over-run braking system AL-KO anti-sway coupling AL-KO wind-down stabiliser legs AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions)	AL-KO independent rubber suspension (IRS) axle	✓
AL-KO anti-sway coupling AL-KO wind-down stabiliser legs AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	AL-KO shock absorbers	✓
AL-KO wind-down stabiliser legs AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	AL-KO over-run braking system	✓
AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size Caravan Body Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Fintry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions)	AL-KO anti-sway coupling	√
AL-KO 8 inch jockey wheel Drawbar cover, impact resistant ABS Alloy wheels Tyre size Caravan Body Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Fintry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions)	AL-KO wind-down stabiliser legs	✓
Drawbar cover, impact resistant ABS Alloy wheels Tyre size Caravan Body Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	·	✓
Alloy wheels Tyre size 185 R14 C Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	· ·	√
Tyre size Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	·	✓
Caravan Body Side wall skirtings in thermoformed ABS blue Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Fntry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	·	185 R14 C
Side wall skirtings in thermoformed ABS Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) blue blue Finish - Polyester sealed FRP V Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof V Front & rear walls - Impact resistant ABS V Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior V Floor - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior V Integrated aluminium tent profile to side wall perimeter V Luggage door on passenger side (light dimensions)	•	
Finish - Polyester sealed FRP Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	·	blue
Insulation - Combination of XPS styrofoam and EPS styropor to floor, walls and roof Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	-	√
Front & rear walls - Impact resistant ABS Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	·	✓
Side walls & roof - Structural sandwich panel with hail resistant FRP exterior & breathable kiln dried plywood interior Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm		✓
Floor - Structural sandwich panel with breathable kiln dried plywood lower & upper layers, plus insulative central core Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm	· · · · · · · · · · · · · · · · · · ·	✓
Windows - Double glazed acrylic windows with integrated privacy blinds, flyscreens and decorative curtains included Entry door 2-part with integrated flyscreen (51cm wide) ✓ Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm		✓
Entry door 2-part with integrated flyscreen (51cm wide) Integrated aluminium tent profile to side wall perimeter Luggage door on passenger side (light dimensions) 1050 x 280mm		✓
Integrated aluminium tent profile to side wall perimeter ✓ Luggage door on passenger side (light dimensions) 1050 x 280mm	· , , , , , ,	✓
Luggage door on passenger side (light dimensions) 1050 x 280mm		✓
	·	1050 x 280mm
	, , , ,	


Action



361 LT







Interior	
Number of berths	2
Forward cafe style dinette/bed conversion (L x W, cm)	200x204 / 2x 200x66
Kitchen	
Cooktop with 12V starter, includes 2x burners and hinged glass cover	✓
Fridge/freezer 3 way AES (12V, 240V, gas) 106 litres	90 litres
Kitchen sink, with flickmixer	✓
1kg Dry chem powder fire extinguisher	✓
Smoke alarm	✓
Bathroom	
Combined shower/toilet with shower curtain and separate shower head	✓
Acrylic hand basin (fold-down) with flickmixer	✓
Cassette toilet with electric flush	19.3 litres
Plumbing	
Truma BN14 gas/electric hot water system	14 litres
Standard water filler (key lock)	✓
Pressurised town water connection	✓
Electrical Equipment	
House battery, deep cycle fully sealed	100Ah
Battery charger	15 Amp
LED lights throughout	✓
240V double power points throughout	✓
External 240V power inlet and outlet	✓
External 12V power outlet, coaxial aerial outlet & USB charge outlet	✓
Awning LED light	✓
12 pin trailer plug & breakaway system	✓
Heating/Cooling	
Air conditioning system 2.4kW Truma Saphir Comfort RC	✓
Gas Equipment	
Gas cylinder, driver side locker	1x 4.5kg
External BBQ gas bayonet point	✓
Audio/Video	
19" HD LED TV/DVD (mounted in living area)	✓
Winegard Sensar antenna	✓
Bluetooth music receiver	✓
Speakers internal x2	✓

Note: Specifications can change due to continous improvement and are subject to change without notice.

^{*}Weights & measurements are indicative only.